HIGH FRECUENCY PISTOI

The Pistol has a 15m electric cable and a 0.8m transmission shaft which can be connected to

any 42v ENAR converter (for more information see

our products: AFE, AFG-AFD, Boxel). This product is

recommended for jobs requiring high vibration levels

and the freedom to move easily around the jobsite.

Designed & manufactured in Europe

Versatility



The Pistol vibrators from ENAR provide the same benefits as the AFP series.

- -Thermal protection for the stator.
- -Oversized motor.
- -Lubricated using oil for high performance and benefits.
- -Hardened head and neck on the concrete vibrator.
- -No maintenance needed.



+ Light and manageable Ideal for horizontal work/forms.

Specially designed for the users comfort so that they may freely move around the jobsite while vibrating concrete.



+ IP67

Protected against dust and rain.

Resistant aluminium housing.

+ Ergonomic

Reduction of vibrations fed through to the user's hand.

The optional anti-vibration system that reduces the vibrations felt by the user to $0.5m/s^2$.



+ High performance

Motor in head, high performance vibrator.

Ideal for intensive jobs. Offering a high performance of 40m³/h.

TECHNICAL DATA

MODEL	DIAMETER (mm)	LENGTH (mm)	AMPAGE (A)	TOTAL WEIGHT (Kg)	VIBRATIONS TO HAND WITHOUT DAMPER (m/s²)	VIBRATIONS TO HAND WITH DAMPER (m/s²)	PERFORMANCE (m³/h)
MP38 AFP	38	370	8	10	1'18	0'34*	Up to 20
MP5 AFP	50	365	10.5	12	2'02	0,46*	Up to 30
MP6 AFP	58	380	15	14	1'95	0'39*	Up to 35
MP7 AFP	65	370	22	16	2'44	0'49*	Up to 40

- Connection: 42V/3~200Hz
- > Frequency: 12000 v.p.m.
- ≥ 0'8m transmission with 15m cable (other lengths available).
- Optional VAS for anti-vibration to counter white knuckle.
- Optional rubber head for the poker.
- **○** Connections for 240Hz converter are also available.

*Optional VAS for anti-vibration to counter white knuckle.



